

Damp area distribution box E125

Order number: 7340139
 Type: E125



Maximum wiring space - Maximum variability

- Easy to install
- Having up to 22 self-sealing cut-off cable entries for cables up to 5x2.5mm²
- External mounting straps with transverse and longitudinal holes for subsequent alignment

Dimensions

Depth	40 mm
Length	75 mm
Width	75 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Material

Box material	PE
Lid material	PE

Properties

Can be lead sealed	-
Colour	Grey
Degree of protection (IP)	IP54
Free of heavy metals	true
Halogen-free	true
Installation type	SM
PVC-free	true
Silicone-free	true
Stackable	-
Weather-resistant	-

Technical features

Design voltage	400 V
Ground inserts	3
Inserts at the side	12
max. cross section	2,5 mm²
Total inserts	15

Certificates & standards

CE	true
Glow wire test	650 °C
REACH	false
RoHS	true
Standards	• DIN EN 60670-1(VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22)
VDE	true

Accessories

Equipped with	None
---------------	------