

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : PLASTIK 70  
 UFI : DU2X-K87W-600G-DQM2  
 Product code : BDS002139AE  
 Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
 Use of the substance/mixture : Anti Corrosion Products

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

CRC Industries Europe B.V.  
 Touwslagerstraat 1  
 9240 Zele  
 Belgium  
 T +32(0)52/45.60.11 - F +32(0)52/45.00.34  
[hse@crcind.com](mailto:hse@crcind.com) - [www.crcind.com](http://www.crcind.com)

#### 1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11  
 Office hours: 9-17h CET

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Full text of H- and EUH-statements: see section 16	

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Contains :

n-butyl acetate; ethyl acetate; 1-methoxy-2-propanol; monopropylene glycol methyl ether

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.  
 H229 - Pressurised container: May burst if heated.

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)	: H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking. EUH208 - Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6), n-butyl methacrylate (97-88-1). May produce an allergic reaction.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Other information	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.
-------------------	---

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	25 – 50	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
butane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (GB)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	10 – 25	Flam. Gas 1, H220 Press. Gas (Liq.), H280
ethyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	10 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
1-methoxy-2-propanol; monopropylene glycol methyl ether substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6 REACH-no: 01-2119452498-28	< 0.25	Flam. Liq. 2, H225 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317
n-butyl methacrylate	CAS-No.: 97-88-1 EC-No.: 202-615-1 EC Index-No.: 607-033-00-5 REACH-no: 01-2119486394-28	< 0.25	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

### 5.3. Advice for firefighters

Firefighting instructions	: Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.  
Emergency procedures : Ventilate spillage area.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Wear personal protective equipment. Ensure good ventilation of the work station. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container closed when not in use.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

butane (106-97-8)	
United Kingdom - Occupational Exposure Limits	
Local name	Butane
WEL TWA (OEL TWA) [1]	1450 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	600 ppm
WEL STEL (OEL STEL)	1810 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	750 ppm

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>butane (106-97-8)</b>	
Remark	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>n-butyl acetate (123-86-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m <sup>3</sup>
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>ethyl acetate (141-78-6)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Ethyl acetate
IOEL TWA	734 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
IOEL STEL	1468 mg/m <sup>3</sup>
IOEL STEL [ppm]	400 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethyl acetate
WEL TWA (OEL TWA) [1]	734 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	1468 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	400 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	1-Methoxypropanol-2
IOEL TWA	375 mg/m <sup>3</sup>
IOEL TWA [ppm]	100 ppm
IOEL STEL	568 mg/m <sup>3</sup>

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)</b>	
IOEL STEL [ppm]	150 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	1-Methoxypropan-2-ol
WEL TWA (OEL TWA) [1]	375 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	100 ppm
WEL STEL (OEL STEL)	560 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	150 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Methyl methacrylate
IOEL TWA [ppm]	50 ppm
IOEL STEL [ppm]	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Methyl methacrylate
WEL TWA (OEL TWA) [1]	208 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	416 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>n-butyl acetate (123-86-4)</b>	
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>n-butyl acetate (123-86-4)</b>	
<b>PNEC (Soil)</b>	
PNEC soil	0.0903 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	35.6 mg/l
<b>ethyl acetate (141-78-6)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	1468 mg/m <sup>3</sup>
Acute - local effects, inhalation	1468 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	63 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	734 mg/m <sup>3</sup>
Long-term - local effects, inhalation	734 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	734 mg/m <sup>3</sup>
Acute - local effects, inhalation	734 mg/m <sup>3</sup>
Long-term - systemic effects, oral	4.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	367 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	37 mg/kg bodyweight/day
Long-term - local effects, inhalation	367 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.24 mg/l
PNEC aqua (marine water)	0.024 mg/l
PNEC aqua (intermittent, freshwater)	1.65 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	1.15 mg/kg dwt
PNEC sediment (marine water)	0.115 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.148 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	0.2 g/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	650 mg/l
<b>1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	553.5 mg/m <sup>3</sup>
Acute - local effects, inhalation	553.5 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	183 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	369 mg/m <sup>3</sup>

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)</b>	
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	33 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	43.9 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	78 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	10 mg/l
PNEC aqua (marine water)	1 mg/l
PNEC aqua (intermittent, freshwater)	100 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	52.3 mg/kg dwt
PNEC sediment (marine water)	5.2 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	4.59 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Vinyl polyalcohol protective gloves.

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: A



# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2.4. Thermal hazards

#### Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: Propane/butane propelled liquid.
Odour	: Solvent.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: -4 °C (closed cup)
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: Not available
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0.919 g/cm <sup>3</sup> at 20 °C
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 75 – 100 %

#### 9.2.2. Other safety characteristics

VOC content : 700 g/l

Additional information : For aerosols data for the product without propellant.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid temperatures exceeding the flash point.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity (oral)** : Not classified (Based on available data, the classification criteria are not met)  
**Acute toxicity (dermal)** : Not classified (Based on available data, the classification criteria are not met)  
**Acute toxicity (inhalation)** : Not classified (Based on available data, the classification criteria are not met)

#### n-butyl acetate (123-86-4)

LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	23.4 mg/l/4h

#### ethyl acetate (141-78-6)

LD50 oral	4934 mg/kg bodyweight
LD50 dermal rabbit	> 20000 (<) mg/kg bodyweight

#### 1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

LD50 oral rat	4016 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 25.8 mg/l

#### methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

LD50 oral rat	7900 mg/kg
LD50 dermal rabbit	> 5000 mg/kg bodyweight

#### n-butyl methacrylate (97-88-1)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	11300 mg/kg

**Skin corrosion/irritation** : Not classified (Based on available data, the classification criteria are not met)  
pH: Not applicable

#### n-butyl acetate (123-86-4)

pH	6.2
----	-----

**Serious eye damage/irritation** : Causes serious eye irritation. (Based on available data, the classification criteria are not met)  
pH: Not applicable

#### n-butyl acetate (123-86-4)

pH	6.2
----	-----

**Respiratory or skin sensitisation** : Not classified (Based on available data, the classification criteria are not met)  
**Germ cell mutagenicity** : Not classified (Based on available data, the classification criteria are not met)  
**Carcinogenicity** : Not classified (Based on available data, the classification criteria are not met)  
**Reproductive toxicity** : Not classified (Based on available data, the classification criteria are not met)

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

**STOT-single exposure** : May cause drowsiness or dizziness. (Based on available data, the classification criteria are not met)

<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>ethyl acetate (141-78-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>n-butyl methacrylate (97-88-1)</b>	
STOT-single exposure	May cause respiratory irritation.

**STOT-repeated exposure** : Not classified (Based on available data, the classification criteria are not met)

<b>n-butyl acetate (123-86-4)</b>	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
<b>ethyl acetate (141-78-6)</b>	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight
<b>1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)</b>	
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight
<b>n-butyl methacrylate (97-88-1)</b>	
NOAEL (oral, rat, 90 days)	120 mg/kg bodyweight

**Aspiration hazard** : Not classified (Based on available data, the classification criteria are not met)

<b>PLASTIK 70</b>	
Vaporizer	Aerosol
<b>n-butyl acetate (123-86-4)</b>	
Viscosity, kinematic	0.83 mm <sup>2</sup> /s
<b>1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)</b>	
Viscosity, kinematic	1.848 mm <sup>2</sup> /s
<b>methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)</b>	
Viscosity, kinematic	0.561 mm <sup>2</sup> /s
<b>n-butyl methacrylate (97-88-1)</b>	
Viscosity, kinematic	1.06 mm <sup>2</sup> /s

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

#### 11.2.2. Other information

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

#### **n-butyl acetate (123-86-4)**

LC50 - Fish [1]	18 mg/l
EC50 - Crustacea [1]	44 mg/l
EC50 72h - Algae [1]	674.7 mg/l
LOEC (chronic)	47.6 mg/l
NOEC (chronic)	23.2 mg/l
NOEC chronic algae	200 mg/l

#### **ethyl acetate (141-78-6)**

LC50 - Fish [1]	230 mg/l
EC50 - Other aquatic organisms [1]	717 mg/l Daphnia magna (Water flea)
NOEC (chronic)	2.4 mg/l 21 d

#### **1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)**

LC50 - Fish [1]	6812 mg/l
LC50 - Fish [2]	20800 mg/l
EC50 - Crustacea [1]	21100 – 25900 mg/l
EC50 - Other aquatic organisms [1]	2954 mg/l
ErC50 algae	> 1000 mg/l

#### **methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)**

LC50 - Fish [1]	368.1 mg/l
EC50 - Crustacea [1]	69 mg/l
EC50 72h - Algae [1]	> 110 mg/l
LOEC (chronic)	68 mg/l
NOEC (chronic)	37 mg/l
NOEC chronic fish	9.4 mg/l

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>n-butyl methacrylate (97-88-1)</b>	
LC50 - Fish [1]	11 mg/l
LC50 - Fish [2]	5.57 mg/l
EC50 - Crustacea [1]	32 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	31.2 mg/l

### 12.2. Persistence and degradability

<b>PLASTIK 70</b>	
Persistence and degradability	Not established. No data is available on the degradability of this product.

### 12.3. Bioaccumulative potential

<b>PLASTIK 70</b>	
Partition coefficient n-octanol/water (Log Kow)	Not applicable
<b>n-butyl acetate (123-86-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.3
<b>ethyl acetate (141-78-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.7
<b>1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)</b>	
Bioconcentration factor (BCF REACH)	< 100
Partition coefficient n-octanol/water (Log Pow)	0.37
<b>methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.38
<b>n-butyl methacrylate (97-88-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.88

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

Additional information : No other effects known  
Global warming potential (GWP) : 1 (Fluorinated greenhouse gases - (EC) No 517/2014)

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878






### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW) code : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

#### 14.6. Special precautions for user

##### Overland transport

Classification code (ADR) : 5F  
Special provisions (ADR) : 190, 327, 344, 625  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E0  
Packing instructions (ADR) : P207, LP200  
Special packing provisions (ADR) : PP87, RR6, L2  
Mixed packing provisions (ADR) : MP9  
Transport category (ADR) : 2  
Special provisions for carriage - Packages (ADR) : V14  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12  
Special provisions for carriage - Operation (ADR) : S2  
Tunnel restriction code (ADR) : D

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

### Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### VOC Directive (2004/42)

VOC content : 700 g/l

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration



# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6), n-butyl methacrylate (97-88-1). May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2

# PLASTIK 70

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Full text of H- and EUH-statements:

Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.