

Lötspitzen

für WSP 80, WSP 80 FE und MPR 80



WSP 80 (FE)



MPR 80

Beschreibung	Breite A	Dicke B	Modell	Best. Nr.			
				Standard-Lote	hochschmelzende Lote	bleifreie Lote	
Rundform		0,25 mm	LT 1	5 44 435 99	-	-	
Langform konisch		0,2 mm	LT 1L	5 44 423 99	-	-	
Rundform		0,2 mm	1,6 mm	LT 1S	5 44 436 99	-	-
Rundform		1,6 mm		LT AS	5 44 404 99	-	-
Rundform		3,2 mm		LT CS	5 44 411 99	-	-
Meisselform		0,8 mm	0,4 mm	LT H	5 44 437 99	-	-
		0,8 mm	0,4 mm	LT H HPB		5 44 430 99	-
Rundform abgeschrägt		1,2 mm		LT F	5 44 408 99	-	-
Meisselform		1,2 mm	0,4 mm	LT K	5 44 438 99	-	-
Meisselform		1,6 mm	0,7 mm	LT A	5 44 440 99	-	-
		1,6 mm	0,7 mm	LT A HPB		5 44 431 99	-
Flachform lang		2,0 mm	1,0 mm	LT L	5 44 414 99	-	-
Flachform		2,4 mm	0,8 mm	LT B	5 44 405 99	-	-
		2,4 mm	0,8 mm	LT B HPB		5 44 432 99	-
		2,4 mm	0,8 mm	LT B LL		-	5 44 446 99
Flachform		3,2 mm	0,8 mm	LT C	5 44 407 99	-	-
		3,2 mm	0,8 mm	LT C LL		-	5 44 447 99
Flachform lang		3,2 mm	1,2 mm	LT M	5 44 415 99	-	-
Flachform		4,6 mm	0,8 mm	LT D	5 44 409 99	-	-
		4,6 mm	0,8 mm	LT D LL		-	5 44 448 99
Rundform abgeschrägt		1,2 mm		LT 4	5 44 439 99	-	-

Lötspitzen

für WSP 80, WSP 80 FE und MPR 80



WSP 80 (FE)



MPR 80

Beschreibung		Breite A	Dicke B	Modell	Best. Nr. Standard-Lote
Lotdepotspitze		2,4 mm	3, 2 mm	LT GW	5 44 410 99
Langform konisch		0,4 mm		LT S	5 44 406 99
Langform gebogen		0,2 mm		LT 1LX	5 44 424 99
Flachform gebogen		0,8 mm	0,4 mm	LT HX	5 44 420 99
		1,6 mm	0,7 mm	LT ALX	5 44 443 99
		2,4 mm	0,8 mm	LT BX	5 44 442 99
Flachform gebogen		1,2 mm	0,4 mm	LT 4X	5 44 428 99
Flachform gebogen		1,6 mm	0,8 mm	LT AX	5 44 427 99
Rundform gebogen		2,0 mm	0,4 mm	LT 1X	5 44 425 99
Rundform gebogen		2,0 mm	0,4 mm	LT 1SLX	5 44 426 99
Rundform abgeschrägt		2,4 mm	4,0 mm	LT BB	5 44 444 99
		3,2 mm	6,0 mm	LT CC	5 44 445 99
LT Entlötipitze		10,5 mm	0,6 mm		5 44 429 99
LT Adapter für SMD-Spitzen		13,5 mm			5 44 417 99
LT Messspitze					5 44 446 00