

LH03 Series of Products interconvert:

2SK30A

Silicon N-Chinnel Junction FET


■ **Application:**

For charge sensor, meter amplifier circuit, rheostat , chopper and gain controller for AGC , electronic switch.


■ **Absolute Maximum Ratings (Ta=25℃)**

Parameter	Symbol	Ratings	Unit
Gate to Drain voltage	V _{GDO}	-50	V
Gate to Source voltage	V _{GSO}	-50	V
Gate current	I _G	10	mA
Allowable power dissipation	P _D	250	mW
Junction Temperature	T _j	125	℃
Storage Temperature	T _{stg}	-55 to +125	℃

Symbol :



Package example:



Package	D	S	G
SC-59			
SOT-23			
TO-92S			
* TO-92	3	1	2
TO-18			

■ **Electrical Characteristics (Ta=25℃)**

Prameter	Symbol	Conditions	min	typ	max	Unit
Drain to Source cut-off current	I _{DSS}	V _{DS} = 10V, V _{GS} = 0V	0.3		6.5	mA
Gate to Source leakage current	I _{GSS}	V _{GS} = -30V, V _{DS} = 0V			-1.0	nA
Gate to Drain voltage	V _{GDS}	I _G = -100μA, V _{DS} = 0V	-50			V
Gate to Source cut-off voltage	V _{GS(OFF)}	V _{DS} = 10V, I _D = 0.1μA	-0.4		-5.0	V
Forward transfer admittamce	Y _{fs}	V _{DS} =10V, V _{GS} =0V, f=1KHZ	1.2			mS
Input capacitance (Common Source)	C _{iss}	V _{DS} =10V, V _{GS} =0V, f=1MHZ		8.2		pF
Reverse transfer capacitance (Common Source)	C _{rss}			2.6		pF

■ **I_{DSS} Rank Classification**

Runk	R	O	Y	GR
I _{DSS} (mA)	0.3 to 0.75	0.6 to 1.4	1.2 to 3.0	2.6 to 6.5
Marking Symbol	035D	035E	035F	035G