


SWITCH FUNCTION	
POS. 1	POS. 2
ON	ON
1-2; 4-5; 7-8	2-3; 5-6; 8-9



- NOTE:
- ALL DIMENSIONS IN MM [INCH]
 - GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 - TERMINAL NUMBERS FOR REF ONLY
 - CONTACT MATERIAL: SILVER
 - RATING: 1A @ 9 VDC
 - ELECTRIC LIFE: 30,000 CYCLES
 - INSULATION RESISTANCE: 100 MEGA-OHM MIN @ 500VDC.
 - ACTUATION FORCE: 3000 ± 800gf
 - TRAVEL: 5.0mm
 - CONTACT RESISTANCE: 50 MILLI-OHM MAX. INITIAL
 - DIELECTRIC STRENGTH: 500 V RMS @ SEA LEVEL.
 - OPERATING TEMP.: -10°C to 70°C
 - ▲ DENOTES CRITICAL PARAMETER.
 - 2011/65/EC (ROHS) COMPLIANT.
 - HARDWARE TO BE SHIPPED BULK:
T081101 - LOCK WASHER, QTY 1
T100025 - WASHER, QTY 1
T081102 - HEX NUT, QTY 2



TITLE FS57003PLT2B2M1QE H

A	22675	New Release	1/16/17	rc
REV	PCR NO	DESCRIPTION	DATE	BY

SCALE	DATE	DR	DWG	REV
1:1	1/16/2017	rc	ST790000	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED