

2-Channel Power Unit, 200 W (255 W)

Item No: T0053422399N



KEY FEATURES

- + Power unit WX 2, with 2 channels, soldering irons WXMP and 1 tweezers WXMT
- + Robust touch screen with ESD safe glas
- + Intuitive use with turn-click-wheel with enter key and finger guide.
- + Blue LED backlighting
- + Multilingual menu navigation
- + High funcionality
- + No safety rest with Stop & Go function needed thanks to integrated acceleration sensor
- + Optimized precision, better stability by sensor in the soldering iron
- + Specific parameterization of tool by storage medium in hand piece
- + Visual process control via blue LED ring light

TECHNICAL DATA

Width	154.0 mm
Height	135mm
Length	174.0 mm
Dimensions L x W x H	174.0 x 154.0 x 135.0mm
Automatic Tool Identification	Yes
Benchtop Controller	Yes
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3,5 mm pawl socket on back of device
ESD Safe	Yes
Fuse	T2A
Interface	1x USB, 2x RS232, 1x Switching Output
Multilingual Display	Yes
Number of Channels	2
Power	200 W (255 W)
Temperature Accuracy °C	±9 °C
Temperature Accuracy °F	±17 °C
Temperature Range (Depends on Tool)	Adjustable from 50°C - 550°C (150°F - 999°F) Adjustable temperature range varies among tools
Temperature Range °C	100 - 550 °C
Temperature Range °F	200 - 999 °F
Temperature Stability °C	±2 °C
Temperature Stability °F	±4 °F
Traceability	Yes
USB	USB interface in front of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Voltage	230 V